WONDERLAY
QUALITY CARPET UNDERLAY

TYPICAL PHYSICAL PROPERTIES	
Name	Wonderlay Gold
Product Code	750501
Thickness (mm)	10
Nominal Density (kg/m³)	120
Laminate (Topside)	Gold Laminate (Polyethylene) Polypropylene Mesh
AS 4288 - 2003 Classification	Luxury - L
Foam	Rebonded Polyurethane
Thermal Insulation	R 0.26 Thermal resistance is a measure of a material's ability to resist heat transfer. The higher the R-value, the better heat transfer resistance of that material.
Acoustic Performance	26 dB The minimum requirement as set by the NCC is 62 dB. (The lower the dB result for the flooring assembly, the better the acoustic performance).
Country of Origin	China

PACKING INFORMATION					
	Length (m)	**Width (m)**	**Area (m²)**	**Weight (kg)**	**Wrap**
Individual Rolls	10	1.80	18	22	Gold Wrap & Black Print Polyethylene

Wonderlay is a Registered trade name.
All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Industry Purchasers assume all risk and liability resulting from the use of this product and must confirm the suitability thereof by their own test. Conditions of Sale contain a limited warranty against manufacturing defects. For full details please contact your Wonderlay sales representative.

WONDERLAY
QUALITY CARPET UNDERLAY